

POWER OUTLET SURGE PROTECTOR

POSP1-01
POSP1-03

Description

MARSA models featuring all mode protection for all combination of line (L-N, L-E, and N-E) that ensure the maximum level protection is achieved at all time. They have designed for installation in any wiring system worldwide.

Features and Benefits

- The surge protectors are made of metal enclosures.
- High safety standard requirement.
- Used for any wiring system.

Application

Use before the connection of power supply to the electrical appliance.



Selection Guide

POWER OUTLET SURGE PROTECTOR



STANDARD OF REFERENCES

- MS IEC 61643-1
- MS IEC 61643-12
- IEEE C62.41
- BS 6651



SPECIFICATION

Power Outlet Surge Protector

SPECIFICATION	POSP1-01	POSP1-03
Description	Plug Switch	
Protection Mode	Full Mode (L-N, L-E, N-E)	
Connection type	Series	
Protection Stage	Multistage	
Nominal Voltage, (Un)	230/240V AC RMS	
Max Working Voltage, (Uc)	275V AC RMS	
Max Load Current	13A	
Working Frequency	40-60 Hz	
Working Temperature	-40°C up to 85°C	
Working Humidity	0-90%	
Max Discharge Current Imax (8/20µs)	10KA	
Let Through Voltage , (Up)	300V	
Standard of References	MS IEC 61643-1 MS IEC 61643-12 IEEE C62.41 BS 6651 IEC 1000-4-5	
Weight	640 g	920 g

DIMENSION



POSP1-01



POSP1-03

Authorized Agent / Distributed By

